

# Tabulars with reledmac

## Sommario

This file provides example of using tabular environments with *reledmac*.  
We use edtabularl, edtabularc and edtabularr, with marginal, critical and familiar notes. We also use optional arguments of \pstart.

### 1 Left align

1	linea prima	linea prima	sidenote l
2	linea secunda	linea secunda <sup>1</sup>	sidenote l
3	linea tertia	linea tertia	sidenote l
4	linea quarta	linea quarta	
5	linea quinta	linea quinta <sup>1</sup>	
6	linea sexta	linea sexta	
7			

### 2 Center align

8	linea prima	linea prima	
9	linea secunda	linea secunda <sup>2</sup>	sidenote c
10	linea tertia	linea tertia	sidenote c
11	linea quarta	linea quarta	sidenote c
12	linea quinta	linea quinta <sup>2</sup>	
13	linea sexta	linea sexta	
14			

---

<sup>1</sup>familiar footnote A.  
<sup>2</sup>familiar footnote A.

---

<sup>1</sup>familiar footnote B.  
<sup>2</sup>familiar footnote B.

---

3 tertia ] critical note A  
10 tertia ] critical note A

---

4 quarta ] critical note B  
11 quarta ] critical note B

### 3 Right align

15		linea prima	linea prima
sidenote16		linea secunda	linea secunda <sup>3</sup>
sidenote17		linea tertia	linea tertia
sidenote18		linea quarta	linea quarta
19		linea quinta	linea quinta <sup>3</sup>
20		linea sexta	linea sexta
21			

---

<sup>3</sup>familiar footnote A.

---

<sup>3</sup>familiar footnote B.

---

17 tertia ] critical note A

---

18 quarta ] critical note B